

Single Tag Printer

Jupiter 712

Type F2

For
Single
Tags

Tags
with
String

Efficient
Tag
Feeding

Printing
Width
64mm

150mm
/sec

LAN
Optional



Best for Brand Tag with String
Max. Printing Speed 150mm/s
LAN connect Interface (Optional)
Hi-Speed and Stable Tag Feeding



Environmental Friendly

RoHS COMPLIANT

C.M.M

Model	JP-712F2
Printing Method	Thermal Transfer Dot Matrix
Printing Density	12dots/mm(300dpi)
Printing Speed	80 to 150mm/second
Printing Width	Max. 64mm
Printing Length	Max. 110mm
Number of Print Head	1
Interface	USB2.0、Optional: LAN connector
Applicable Barcodes	JAN(13 . 8) 、EAN UPC/A、UPC/E、2of5(Industrial) NW7、Code39、Code93、Code128 ITF、GS1-128、GS1 Databar PDF417、QR-code DataMatrix(ECC200)、GS1 Composite
Media Type	Single-sheet Tags (with threads)
Printable Tag Width	20 to 105mm
Printable Length	200mm
Overall Size	W385 x D315 x H355
Weight	23kg
Power Source	AC100V/220V 50/60Hz
Power Consumption	Less than 400VA
Accessories	Operation Manual、AC cord

MADE IN JAPAN

High-Reliability of Japanese Quality