

Single Tag Printer

Jupiter 712

Type F2

For
Single
Tags

Tags
with
String

Efficient
Tag
Feeding

Printing
Width
64mm

150mm
/sec

LAN
Optional



Best for Brand Tag with String
Max. Printing Speed 150mm/s
LAN connect Interface (Optional)
Hi-Speed and Stable Tag Feeding



Environmental Friendly

RoHS COMPLIANT

C.M.M

| | |
|----------------------|--|
| Model | JP-712F2 |
| Printing Method | Thermal Transfer Dot Matrix |
| Printing Density | 12dots/mm(300dpi) |
| Printing Speed | 80 to 150mm/second |
| Printing Width | Max. 64mm |
| Printing Length | Max. 110mm |
| Number of Print Head | 1 |
| Interface | USB2.0, Optional: LAN connector |
| Applicable Barcodes | JAN(13 . 8) , EAN UPC/A, UPC/E, 2of5(Industrial) NW7, Code39, Code93, Code128 ITF, GS1-128, GS1 Databar PDF417, QR-code DataMatrix(ECC200), GS1 Composite |
| Media Type | Single-sheet Tags (with threads) |
| Printable Tag Width | 20 to 105mm |
| Printable Length | 200mm |
| Overall Size | W385 x D315 x H355 |
| Weight | 23kg |
| Power Source | AC100V/220V 50/60Hz |
| Power Consumption | Less than 400VA |
| Accessories | Operation Manual, AC cord |

MADE IN JAPAN

High-Reliability of Japanese Quality